



# **Università degli Studi di Napoli "*Parthenope*"**


## **Dipartimento di Scienze e Tecnologie**

### ***Tecnologia delle costruzioni ed allestimento navale***


Vincenzo Piscopo

Analisi di dettaglio dei disegni strutturali di una nave bulk carrier – Parte III  
Lezione 13 (26/48)

## 1.1 Vista longitudinale



# 1.2 Ordinata comune: vista di insieme



- NOTES:**
- 1) SIDES ARE SYMMETRIC UNLESS OTHERWISE SHOWN.
  - 2) THE PLANS, SECTIONS AND ELEVATIONS ARE SHOWN IN LOOKING DOWNWARD, FORWARD AND PORT RESPECTIVELY.
  - 3) MATERIAL:
    - a) NO MARKED STEEL: GRADE "A" MILD STEEL (Y = 235 N/mm<sup>2</sup>)
    - b) MARKED "D" : GRADE "D" MILD STEEL (Y = 235 N/mm<sup>2</sup>)
    - c) MARKED "AH" : GRADE "A" H.T. STEEL (Y = 315 N/mm<sup>2</sup>)
    - d) MARKED "DH" : GRADE "D" H.T. STEEL (Y = 315 N/mm<sup>2</sup>)
    - e) MARKED "AH36" : GRADE "A" H.T. STEEL (Y = 355 N/mm<sup>2</sup>)
    - f) MARKED "DH36" : GRADE "D" H.T. STEEL (Y = 355 N/mm<sup>2</sup>)
    - g) MARKED "EH36" : GRADE "E" H.T. STEEL (Y = 355 N/mm<sup>2</sup>)
  - 4) STIFFENER END CONNECTION:
    - h) S : END SNIPPED
    - i) B : BRACKET CONNECTION
    - j) NO MARKED (OR W): WELDED CONNECTION

- NOTES:**
- 1) SIDES ARE SYMMETRIC UNLESS OTHERWISE SHOWN.
  - 2) THE PLANS, SECTIONS AND ELEVATIONS ARE SHOWN IN LOOKING DOWNWARD, FORWARD AND PORT RESPECTIVELY.
  - 3) MATERIAL:
    - a) NO MARKED STEEL: GRADE "A" MILD STEEL (Y = 235 N/mm<sup>2</sup>)
    - b) MARKED "D" : GRADE "D" MILD STEEL (Y = 235 N/mm<sup>2</sup>)
    - c) MARKED "AH" : GRADE "A" H.T. STEEL (Y = 315 N/mm<sup>2</sup>)
    - d) MARKED "DH" : GRADE "D" H.T. STEEL (Y = 315 N/mm<sup>2</sup>)
    - e) MARKED "AH36" : GRADE "A" H.T. STEEL (Y = 355 N/mm<sup>2</sup>)
    - f) MARKED "DH36" : GRADE "D" H.T. STEEL (Y = 355 N/mm<sup>2</sup>)
    - g) MARKED "EH36" : GRADE "E" H.T. STEEL (Y = 355 N/mm<sup>2</sup>)
  - 4) STIFFENER END CONNECTION:
    - h) S : END SNIPPED
    - i) B : BRACKET CONNECTION
    - j) NO MARKED (OR W): WELDED CONNECTION

PRINCIPAL DIMENSIONS			
LENGTH	(B.P.)	172.00 M	
LENGTH	(SCANTLING)	170.48 M	
BREADTH	(MLD.)	30.00 M	
DEPTH	(MLD.)	14.70 M	
DRAUGHT MLD.	(DESIGN)	9.00 M	
DRAUGHT MLD.	(SCANT.)	9.90 M	
SERVICE SPEED		14.0 Knots	


PRINCIPAL DIMENSIONS			
LENGTH	(B.P.)	172.00 M	
LENGTH	(SCANTLING)	170.48 M	
BREADTH	(MLD.)	30.00 M	
DEPTH	(MLD.)	14.70 M	
DRAUGHT MLD.	(DESIGN)	9.00 M	
DRAUGHT MLD.	(SCANT.)	9.90 M	
SERVICE SPEED		14.0 Knots	

35,000 DWT CLASS BULK CARRIER	
TYPICAL ORDINARY SECTION	

35,000 DWT CLASS BULK CARRIER	
TYPICAL ORDINARY SECTION	




# 1.2 Ordinata comune: strutture del fondo




# 1.2 Ordinata comune: strutture del ponte

Ordinary section at frame 138  
frame spacing: 800 mm



STIFFENERS		
LOCATION	NO.	SCANTLINGS
UPPER DECK	13 - 17	350 x 13 + 150 x 22 (T) "AH36"
	1 - 16	250 x 90 x 12 / 16 A "AH"
	17 - 20	250 x 90 x 10 / 15 A "AH"
BOTTOM & SIDE SHELL	23 - 25	300 x 13 + 100 x 22 (T) "AH36"
	23 - 28	300 x 13 + 100 x 22 (T) "AH36"
TOP SIDE WING TK. BTM.	1 - 12	300 x 90 x 11 / 16 A "AH36"
	16 - 19	300 x 90 x 11 / 16 A "AH"
	20	250 x 90 x 12 / 16 A "AH"
CENT. GIRD.	1	250 x 90 x 12 / 16 A "AH"
HATCH COAMING	1 - 2	200 x 90 x 10 x 14 I.A.
	3	450 x 15 + 150 x 16 (L)

# 1.3 Ordinata rinforzata: vista di insieme



- NOTES:**
- 1) SIDES ARE SYMMETRIC UNLESS OTHERWISE SHOWN.
  - 2) THE PLANS, SECTIONS AND ELEVATIONS ARE SHOWN IN LOOKING DOWNWARD, FORWARD AND PORT RESPECTIVELY.
  - 3) MATERIAL:
    - a) NO MARKED STEEL: GRADE "A" MILD STEEL ( $Y = 235 \text{ N/mm}^2$ )
    - b) MARKED "D" : GRADE "D" MILD STEEL ( $Y = 235 \text{ N/mm}^2$ )
    - c) MARKED "AH" : GRADE "A" H.T. STEEL ( $Y = 315 \text{ N/mm}^2$ )
    - d) MARKED "DH" : GRADE "D" H.T. STEEL ( $Y = 315 \text{ N/mm}^2$ )
    - e) MARKED "AH36" : GRADE "A" H.T. STEEL ( $Y = 355 \text{ N/mm}^2$ )
    - f) MARKED "DH36" : GRADE "D" H.T. STEEL ( $Y = 355 \text{ N/mm}^2$ )
    - g) MARKED "EH36" : GRADE "E" H.T. STEEL ( $Y = 355 \text{ N/mm}^2$ )
  - 4) STIFFENER END CONNECTION:
    - h) S : END SNIPPED
    - i) B : BRACKET CONNECTION
    - j) NO MARKED (OR W) : WELDED CONNECTION

FLOOR SCANTLINGS							
HOLD N° 3				HOLD N° 2 & 4			
FRAME	①	②	③	FRAME	①	②	③
139	12.0	13.0	13.0	173 & 105	12.5	12.5	12.5
136 & 112	13.0 "AH 36"	11.5	11.0	170 & 146 & 102 & 78	13.5 "AH 36"	11.5	11.0
133 & 115	14.0 "AH 36"	13.5	11.5	167 & 149 & 99 & 81	14.5 "AH 36"	12.5	11.5
130 & 118	15.0 "AH 36"	13.0	12.0	164 & 152 & 96 & 84	15.0 "AH 36"	13.0	12.0
127 & 121	16.0 "AH 36"	12.5 "AH"	12.5	161 & 155 & 93 & 87	15.5 "AH 36"	13.0	12.0
124	17.0 "AH 36"	13.0 "AH"	12.5	159 & 90	15.5 "AH 36"	13.0	12.0


FLOOR STIFF.: 150 x 12 EXC. AS SHOWN

PRINCIPAL DIMENSIONS		
LENGTH (B.P.)		172.00 M
LENGTH (SCANTLING)		170.48 M
BREADTH (MLD.)		30.00 M
DEPTH (MLD.)		14.70 M
DRAUGHT MLD. (DESIGN)		9.00 M
DRAUGHT MLD. (SCANT.)		9.90 M
SERVICE SPEED		14.0 Knots

35,000 DWT CLASS BULK CARRIER

TYPICAL WEB SECTION

## 1.3 Ordinata rinforzata: strutture del fondo












## 1.4 Paratia corrugata: strutture del fondo



## 1.4 Paratia corrugata: strutture del ponte

### Bhd. section at frame 141

CORRUGATED BULKHEAD THICKNESS: 20.5 "AH"  
(EXC. AS SHOWN)

